



## ADVANCED MOBILE SURVEILLANCE

Transportation environments can often prove harsh for electronic equipment, with exposure to repetitive shocks and vibration proving too much for some electronic systems. Specifically designed for public and commercial transport applications and encased in a ruggedised metal chassis, the TransVu unit can withstand this tough environment to provide uninterrupted invehicle security surveillance.

### RUGGED DESIGN

Designed to conform to ETSI 5M2 (road) and EN 61371 (rail) standards with an anodised aluminium enclosure and aerospace grade suspension bushes, the TransVu can withstand prolonged exposure to the vibration and shock that is typical of road and rail transportation. In addition, the use of rugged multi pin automotive connectors provides good quality connections even with continuous vibration and allows quick and easy removal / installation.

### TRANSVU MEDIA

The TransVu Media variant allows advertising or customer information to be shown to commuters. User programmable, TransVu Medias' messaging system uses industry standard programming languages such as Javascript. The messaging

can be location specific, advertising shops or attractions on the vehicles route. In addition text can be overlaid with the images to add specific messages to customers. Additional revenue benefits can be realised by deploying a flexible advertising solution such as this.

### LOGGING OF VEHICLE SYSTEMS

TransVu supports logging of vehicle systems such as engine speed, vehicle speed, use of indicators, brakes etc. Harsh braking and turning are logged as events, the on board accelerometer constantly logs these forces and on playback displays on screen graphs accurately displaying turning, accelerating and braking forces.

### GPS

Through the use of an optional GPS unit, positional information can be relayed to a control room which may be integrated with moving map displays. GPS routes can be created and vehicles that are "off route" can be tracked and intercepted, ideal for security applications or where vehicles need to remain on a set route. The TransVu can include an integrated GPS module or support an external GPS module via serial connectivity.

# FEATURES

- ❑ Mobile DVR specifically developed for public and commercial transport applications
- ❑ 8, 12 or 16 camera inputs
- ❑ IP and Megapixel Camera compatible
- ❑ Record Rate of 200pps across unit
- ❑ GPS, accelerometer and vehicle systems data all linked to video footage
- ❑ Option for 2nd Ethernet port for AOE storage or IP camera connections
- ❑ Programmable LED indicator outputs
- ❑ Real time multi screen display output for all cameras in live and playback
- ❑ Full Configuration of the product via on board monitor GUI.
- ❑ Internal Buzzer to signal video loss or HDD alarm (user configurable)
- ❑ Ignition controlled shut-down with configurable time delay
- ❑ Audio output for on-board multi-media or passenger announcements
- ❑ Low power consumption
- ❑ Removable hard drives
- ❑ 3 axis - 2G / 8G full deflection auto configurable accelerometer, (enables product mounting in any orientation)
- ❑ Heater option available for extreme cold climates
- ❑ Location tracking via GPS\*
- ❑ Wireless LAN Compatible
- ❑ Analytics Capable
- ❑ GSM/SMS/GPRS/UMTS(3G)/HSDPA/HSUPA/HSCSD support\*
- ❑ VGA and Composite local main monitor outputs
- ❑ Spot monitor output
- ❑ VGA or composite monitor output for view / replay or Media output (optional)
- ❑ Optional media support for advertising and public announcements

## SPECIFICATION

### CAMERA INPUTS

8, 12, 16 camera inputs. Camera Masking Detection, Auto detection on power up. Alarm on camera fail. Support for IP and Megapixel cameras

### RECORD RATES

Max 200pps (PAL) across the unit.

### COMPRESSION

JPEG and MPEG-4 format files

### RECORD PROFILES

**MultiMode** recording allows record profiles to be set on a per camera basis

### MONITOR VIEWING

Main Monitor: (VGA or Composite)  
Spot Monitor: 1 (Composite)

### Analytics Capable

AnalyticsCapable products can be upgraded to run a range of Dedicated Micros analytics solutions including; ANPR, Object Left/Removed, Detection Tripwire, Counting Tripwire.

### AUDIO

Line in : 2 x 1v pk-pk or configurable for electret microphone input

Line out: 1 x 1v pk-pk

Local and network audio record and playback

### RECORDING MEDIA

1 or 2 Removable SATA hard drives (in separate, lockable drawers). Up to 2TB of internal storage. Solid state option.

### ALARM INPUTS

8, individually configurable  
(6 pre-configured as alarm inputs, 2 pre-configured as frequency counts)

### AUXILIARY RELAYS

2, independent software control

### ACCELEROMETER

3-axis accelerometer to enable mounting in any orientation

### THIRD PARTY INTEGRATION

PowerScript feature assists in the integration between the TransVu and third party products enabling powerful unique applications to be created.

### TRANSVU STATUS MODULE

Provides visual messages to the vehicle operator as to the status of various components of the TransVu unit. Status messages include; power status, camera fail, recording status, alarm status and camera masking. The module is available as an optional accessory.

### PANIC BUTTON

Striking a driver's panic button instantly alerts a central control station and can transmit images of an emergency over any network the TransVu is connected to.

### RAPID DEPLOYMENT

The low current consumption required for operation combined with the units mobility makes the TransVu product range ideal for rapid deployment applications where solar power with backup batteries provides the power.

### RESOLUTION

QCIF, CIF, 2CIF and 4CIF resolution

### DATA PORTS

Serial Ports 1 x RS485, 1 x RS485/RS422 and 3x RS232 - can be used for interface to external GPS GPRS or modems or Telemetry control of cameras  
Ethernet: Single or Dual Ethernet ports 10/100  
USB: 2 x USB 2.0 Connector for archive, USB mouse, or touch screen monitors  
GPS: 1x RF Connector

### ENCLOSURE

IP65 minimum  
Anti-vibration mounts  
Mount in any orientation  
Optional heater to enable operation to -20C ambient

### WEIGHTS & MEASURES

Dimensions: 120mm (H) x 253mm (W) x 317mm (D)  
Weight: 6.2 kg (25.1 lbs) (dual removable drive)

### POWER SUPPLY

9 – 42V dc  
12V, 5V individually software switched  
Ignition and low voltage sense. Dedicated input.  
Integrated +12v @ 4A and + 5v @ 2.5A protected PSU for powering external equipment.

### TEMPERATURE RANGE

TransVu (Diskless): -5 to 70 °C / 23 to 158°F  
Disk Drive: 5 to 55 °C / 41 to 131°F  
Solid State Disk Drive: -5 to 70 °C / 23 to 158°F

### EXTENDED OPTIONS

GPS  
Individually managed camera power outputs  
Single or Dual Drive

### WARRANTY

3 years warranty including HDDs.

### APPROVALS

**EMC**  
89/336/EEC, Electromagnetic Compatibility Directive (EMC)  
2004/104/EC Automotive Directive  
BS EN 61000-6-1:2001  
DD ENV 50204:1996  
BS EN 50081-1:1992  
BS EN 50121-3-2:2000 (referring to EN 55011)  
BS EN 50155:200  
IEC 60571 Ed. 2.0b:1998

### SHOCK AND VIBRATION


IEC 61373:1999  
BS EN 50155:2001  
IEC 60571 Ed. 2.0b:1998  
ETSI EN 300 019-2-5 V2.1.2 (2001-09) Environmental

### TEMPERATURE

IEC 60068-2-1  
IEC 60068-2-2  
BS EN 50155:2001  
IEC 60571:1998

Note: the above approvals refer to current standards. Where appropriate, the latest revisions will be applied to the latest generation of TransVu products.

\* Via Suitable Interface



FOR FURTHER INFORMATION PLEASE CONTACT

PLEASE CHECK THE WEBSITE FOR DETAILS OF COMPATIBLE PRODUCTS AND OTHER LATEST DEVELOPMENTS

[www.transvu.co.uk](http://www.transvu.co.uk)